

PRODUCT

# 2S FUEGO

Upholstery fabric category

**MICROFIBRE**  
with thick lamination

Material

**100% POLYESTER (PES)**

Care label



## QUALITY FEATURES

The product meets the quality requirements of DIN EN 14 465:2006.



Abrasion resistance EN ISO 12947-1 & 2	<b>70,000 rubs</b>
Pilling EN ISO 12945-2 - 2,000 rubs	<b>4</b>
Light fastness EN ISO 105-B02 - Vers. 2	<b>3-4</b>
Fastness to rubbing EN ISO 105-X12	<b>4-5/4</b>
Cigarette test DIN EN 1021-1	<b>passed</b>
Azo dyes	
Aryl amines in accordance with applicable legal provisions EN 14362-1 & 3	<b>not verifiable</b>
Allergenic dispersion dyes in accordance with DIN 54231	<b>not verifiable</b>

Further test results are available from Cotta Collection AG on request.


## COVER PROPERTIES

It is a typical feature, occurring with normal use, that flat woven fabric tends to become fluffy, leading to the formation of lint (pilling). Fibres from other materials can also adhere to the fabric. Use a lint and bobble remover to remove pilling. Pilling is caused by the properties of the fibres and does not constitute grounds for complaint.

Colour transfer from cushions and/or clothing does not represent a defect of the material. Deviations in colour and texture are typical of this type of product and do not constitute grounds for complaint. Interaction of pressure, heat and humidity may lead to pile displacement (pressure marks) to some extent. This property is referred to as indentation or seating marks and is a typical feature that does not represent minor quality in any way.



SAVANNAH F450



STEEL F451




GREY F452




LIGHT BROWN F453



DARK BEIGE F454



CHARCOAL F455



CINNAMON F457



SILVER F458



BROWN F459



OLIVE F461



STANDARD 100 ZH015 181991 TESTEX

www.oeko-tex.com